























# BEST SELECTION

**ALTIA Best Selection** 

2022-2023

### AUTOMOTIVE SERVICE EQUIPMENT













Vehicle washing equipment



equipment



Labor-saving a efficiencyimproving



Body repairing and painting equipment



## Vehicle inspection equipment

Improving the efficiency of vehicle inspection with various vehicle inspection devices from the latest system!

#### **Smart-VIS**

Line controller box



Strives for visibility! Achieves greater efficiency in vehicle inspection! Contributes to prevention of unimplemented inspection and human errors!!

- Contributes to reducing work time by automating vehicle inspection equipment and automatically judging measured values.

  Adopts a graphic design with excellent visibility! Uninspected items and non-conforming items are also clearly

- Achieves accurate printing of record book.

  If there are non-conforming items or uninspected items, the record bo

  Further improves work efficiency and compliance through various optional functions.
- Possible to input the content corresponding to the revision of Exhaust Noise Law



Digital meter









\*\* The digital meter can be selected from stand type, hanging type and retractable type.
\*\* The above illustration of the line controller box is for the vehicle equipped with IM9031-0820 (optional).



IM9832-SV00



By using the 2D ba



Smart VIS





#### OSS (one-stop service) application system (linked type)

### Can be linked to various maintenance systems and OSS application system!

By linking with the OSS application system PC owned by the customer, it is possible to print the "Inspection by Inspection Equipment etc." part of the designated/specified maintenance record book! It contributes to reducing work hours and reducing the burden

% In addition to the above systems, the maintenance system that can be linked can also be linked to other various systems such as VERTICE Extreme and NS21 System.



**SroadLeaf** 








#### What is OSS (one-stop service)?

#### Vehicle inspection efficiency system CAI-EX05

+ Supports the improvement in the overall efficiency of vehicle inspection such as customer management and form creation!

- It is possible to prevent input errors in inspection items and inspection procedures, and to indicate (display) candidates for replacement parts, and save the input data!
- It is possible to print the entire record book and various vehicle inspection related forms! It can be linked to core systems and accounting systems of various automobile manufacturers.









It is possible to print the entire record book with the information (entered into the acceptance PC of CAI-EX05) about vehicle inspection certificate and about work instructions and results of inspection items, as well as the information about inspection results transferred from Smart-VIS. In addition, by printing the legal documents required for vehicle inspection, it will greatly improve efficiency and strengthen compliance in the administrative process of vehicle inspection.

#### Printable documents related to vehicle inspection


- Printing of entire designated maintenance / specific maintenance record book ●Selfcompensation liability application ● Certificate of conformity delivery ledger
- Weight tax payment certificate
   ●Continuous inspection application
   ●Preliminary parts purchase
- Safety standards conformance certificate
   Work instructions





#### Vehicle image capture and saving system

- Reads the license plate with a dedicated camera, and automatically generates a folder with the same name as the license plate!
- Automatically saves vehicle images to generated folder!
- Contributes to enhanced compliance by automatically capturing and saving vehicle images
- Possible to take any image using a tablet and save it in the same folder.
- Achieves a significant reduction in the time required for photo sorting and saving as compared to manual photographing with digital cameras, etc.







#### 4t/10t Side Slip Tester

#### Smart Vis



- Allowable axle load: 4t Dimensions: 2,490 (W) x 570 (D) x 123mm (H) Meter: Digital/hanging type

IM2213-5010

- Allowable axle load: 10t
   Dimensions: 2,860 (W) x 610 (D) x 140mm (H)
   Meter: Digital/hanging type

Product IM2261-5011

Product

IM2201-6010

- Allowable axle load: 10t
   Dimensions: 2,810 (W) x 1,100 (D) x 200mm (H)
   Meter: Digital/hanging type

Product IM2202-6010

- Allowable axle load: 10t Dimensions: 1,470 (W) x 910 (D) x 190mm (H) \* Body dimensions on one side only
- Meter: Digital/hanging type

#### Super Combi Quatt/Front and Rear Axles Connected Super Combi Quatt



■ By connecting the front and rear rollers, it is possible to measure in a state closer to the actual driving!

(For front and rear axles connected type only)

- Even when measuring 4WD vehicles, it is possible to measure without moving the vehicles! (Common to both models)
- Applicable wheelbase: 1,800mm to 3,300mm (Common to both models)

#### **Super Combi Quatt**

IM2538-MV00

 $\ensuremath{\mathbb{X}}$  Since this product is an operating side assembly, it is necessary to install a separate 4t brake + speedometer combo tester

### Smart Vis

#### 4t/10t brake + speedometer combo tester



4t Quiet A·B·S

**Super Multi Tester** 

Product IM2538-C010

- Allowable axle load: 4t
- Dimensions: 2,680 (W) x 1,270 (D) x 240mm (H) ■ Meter: Digital/hanging type

■ Allowable axle load: 4t

4t Qeuit B·S

**Super Combi Tester** 

IM2538-B010


■ Dimensions: 2,680 (W) x 650 (D) x 240mm (H) ■ Meter: Digital/hanging type

Super Combi Tester (Groove Roller Type)

Product IM2599-7011

- Allowable axle load: 10t
- Dimensions: 3,700 (W) x 800 (D) x 520mm (H) Meter: Digital/hanging type





Super Combi Tester (Silent Roller Type)



- Allowable axle load: 10t
- Dimensions: 3,700 (W) x 800 (D) x 520mm (H) Meter: Digital/hanging type

#### **Headlight tester**

#### Altia headlight tester


①Supports downward pointing (low beam) ②Supports fog lamp (lower limit height: 25 cm) ③Equipped with cross-line laser ④Supports HID/LED lamps



#### **Emission tester**

#### UREX-5000V II

- Warm-up time is only 4 minutes!
- Easy calibration for correct measurement at all times







Product EG1802-0000

НС СО

#### 4 gases

Product EG1802-5000 CO CO<sub>2</sub> O<sub>2</sub>

#### 5 gases

Product EG1802-5500

#### Transmission-type smoke meter

#### **Opacity meter**

EG1802-5000



Product IM5050-0000

#### **Compact volume meter** and arrow stand





■ Easy measurement by pinching the inglass with the measuring instrument



PT-500 (with calibration certificate

IM2897-0100



#### 4t/10t free roller



■ Combined with a Super Combi Tester for efficient and safe measurement





#### IM2488-0000

- Dimensions: 2,890 (W) x 1,780 (D) x 290mm (H) ■ Applicable wheelbase: 1,800 - 3,200 mm
- Allowable axle load: 4t (when passing)




IM2594-0000

- Allowable axle load: 10t
  - Dimensions: 3,100 (W) x 850 (D) x 420mm (H)



Full Time Helper

Portable free roller



IM2486-1000

■ Allowable wheel load: 1.000 kg



IM2485-ST00

with IM2485-0000 and IM2486-1000

## **Alignment**

#### For easy operation and speedy alignment measurements!

#### **Current state of driver assistance** technology

Current driver assistance technology has progressed to the "Level 2" stage where the system supports both steering operation and acceleration/deceleration. In Japan, major technological leaps have led to an increasing number of ASVs (advanced safety vehicles) equipped with collision-mitigation brakes and lane-keeping assistance systems, making it mandatory for new passenger cars released after November 2021 to be equipped with automatic brakes.

#### Necessity of alignment adjustment

like this while driving?

- If you don't hold the steering wheel firmly, the car won't go straight.
- It is difficult to drive on a curve...
- Poor fuel economy...
- Uneven wear of tire is terrible...

Have you ever experienced something

**AUTION!** 

It is important to adjust and understand the alignment correctly on a daily basis in order to maximize the ability and drive safely, improve the fuel efficiency and reduce the frequency of tire replacement.

#### What is required to maintain the performance of Advanced Safety Vehicle

In order to maintain the performance of Advanced Safety Vehicles (ASVs), the following procedures must be followed to correct and repair the body

#### Body alignment

For more information, see page 25,

This is the work to correct the body structure (frame) and exterior panel (outer panel) of the vehicle that are deformed due to an accident or the like. The technicians measure the dimensions of the frame and restore it according to the data of the body dimensions drawing from the car manufacturer.

#### Wheel alignment

Check the alignment of tires and suspension, including toe, camber and caster, and check if there is any deviation from the manufacturer's default alignment values. Make adjustments as necessary.

#### Aiming adjustment

For more information, see page 7.


In addition to removing exterior parts with cameras and millimeter-wave radars, and replacing windshields with car etc., the calibration work is performed when painting the outer body panels after frame corrections. It is performed for proper operation of the advanced safety devices

Wheel alignment tester

#### Quick Aligner 3D AutoBoom







% The wheel clamp in this image is wheel-mounted. This product also comes with an enfolding tire clam standard...





#### Measurement flow

#### Place the vehicle on the alignment lift

Place the vehicle on the alignment lift and set it to a height that



#### Inspection before

Check the condition of the car, including whether the air pressure is uniform and whether the tires are worn or scratched.



#### Install a special target to the wheel

Select vehicle mode and enter vehicle information

An enfolding tire clamp should be used! No need to worry about scratching the wheel.



#### Make work easier by using your tablet or smart telephone!



#### Start measurement!

details such as vehicle number.

The camera will autom atically recognize the target. After recognition, follow the on-screen instructions to set the vehicle back and forth and turn the steering wheel left and right

Follow the instructions on your PC to select your vehicle and enter



#### Support your alignment business with the customer management functions



#### Measurement completed!

After the measurement is completed, the measurement results can be checked on the screen, and the measured values before and after adjustment can be printed. In addition, since the measured values are updated in real time, it

is possible to check the values while adjusting the chassis



#### Testimonial from a user who has introduced this product (Plant A in Yamanashi Prefecture)

We have recently introduced the Quick Aligner 3D Autoboom to replace the laser-type alignment tester we have been using for many years. The maximum wheel size we could handle before was 20 inches, but now we can measure up to 24 inch wheels, which is very helpful as it has increased the number of vehicle models we can handle. In addition, since it can display live measured values, and can provide a variety of displays (from the overall display of parameters to the individual magnified display of each axis), and can also display measured values that match adjustment items such as jack-up adjustment, it is very convenient to use. You can now print a report of your measured values and make adjustments while confirming the measured values with the customer.

#### **Wheel Alignment Tester for Large Vehicles** Jumbo 3D SUPER





#### Easy and speedy alignment measurement for large vehicles





Understanding alignment

Tires last longer with the correct alignment measurements! Contributing to improved fuel efficiency!

**Dual monitor** 

measurements before aiming

#### Increased safety awareness even for large vehicles!

### **CHECK!**


First of its kind in the world! Four high-performance 3D cameras enable quick alignment measurements for large vehicles! Exactly!









displayed on your tablet or smartphone! Measured values can also be checked from inside the pit where the screen is difficult to see, contributing to efficient work.



IM2330-0000



#### Runout measurement screen



#### Steering measurement screen



#### Measurement result screen



part of the tester.

Equipped with dual monitor at the lower ou can check and adjust the values even from inside the pit.

#### 3D Alignment Tester V3400

■ Easy! High accuracy! High Spec Alignment Tester



### **Alignment Lift**

■ Alignment lift is essential for alignment measurement and adjustment!



alignment lift MUS30HU

LM4189-0010



LM4174-0000 ent Lift (Pit Type, Red) MUL-27G


LM4174-0P0R

#### Camber Gage Attachment for **Aluminum Wheels**

- Whether it is a wheel that is difficult to attach a magnet or a domestic or overseas model, it can cope with a wide range of wheels!
- Can be installed without damaging the wheel



HG-206



## Specific maintenance and aiming

Shortening work time with the latest aiming tool indispensable for ASV (advanced safety vehicle)

#### What is specific maintenance??


#### ■ Regarding the Bill for Partial Revision of the Road Transport Vehicle Act and Specific Maintenance

The Bill for Partial Revision of the Road Transport Vehicle Law was promulgated on May 24, 2019, and the specific maintenance system came into effect on April 1 2020

(Due to the revision of the inspection standards, considering the impact on the issuance of the safety standards compliance certificate at the designated plant, the inspection standards will be implemented in October 2021)

"Specific maintenance" refers to maintenance that expand the definition to include the following repairs and modifications: In recent years, a dramatically increasing number of advanced safety technologies have been equipped for new vehicles, such as "automatic braking" and "automatic lane keeping". These technologies consist of high-level and complex sensing devices and electronic control devices. When they fail, they can be modified and repaired without removing them (may affect their operation).

The name has been changed from conventional "disassembly and maintenance" to "specific maintenance", which is directly related to the safe operation of the car, and is quite difficult (requires the effective use of the maintenance manuals and scan tools), so the maintenance of electronic control devices has been added.



Compound-eye camera

No need

Camera + millimeter-wave radar combo type

▲An example of a device mounted on a commercial vehicle for sensing the fron

#### What is the work subject to specific maintenance?

The following work (maintenance of electronic control unit) is subject to specific maintenance (= aiming adjustment) as it is directly related to the safe operation of vehicles and it is difficult to perform maintenance work (requires the effective use of the maintenance manuals and scan tools).

- ① Maintenance and modification that may affect the removal and operation of the automatic operation device
- ② Disassembly and functional adjustment of the camera, which is used in the Advanced Emergency Braking System (so-called "automatic braking") and the Automatically Commanded Steering Function (so-called "lane keeping") for sensing the situation ahead (%)
  - makes the ECU recognize that a camera or radar has been connected, or optical axis adjustment without
- 3 Removal and installation of the front part of the vehicle (bumper and grille, to which the camera, radar, etc. related to
  - \* After that, it is necessary to adjust the functions of the camera, etc.

For details on specific maintenance regulations and equipment, please refer to the Certification, Designation, and Specific Maintenance Guidance issued by our company or the homepage of the Ministry of Land, Infrastructure, Transport and Tourism

### What is the essential sensor for ASV (advanced safety vehicle)?

The markets are speeding up the introduction of ASVs (advanced safety vehicles) equipped with collision mitigation brakes, lane keeping assist, and adaptive cruise control. In addition to improving the performance of safety equipment, safety standards for collision mitigation brakes have been clearly established, and the era of "Sensor Fusion", which enables highprecision control via multiple sensors, has arrived.

Therefore, it is required that various sensors be able to be aimed at even in the aiming operation of specific maintenance

#### Camera

Cameras act as a substitute for the human eyes, and now more and more models are equipped with multiple cameras, not just at the back of the room mirror, to control automatic braking (collision

People expect more functions that can replace the human eyes in the future, such as using AI (artificial intelligence) to perform image recognition based on information from cameras, recognize surrounding objects, pedestrians, traffic lights and signs, detect white lines on roads, and collect and process information

#### Millimeter-wave radar

LiDAR

Millimeter-wave radar is used for tracking functions, etc., and ,millimeter-wave refers to extremely high-frequency electromagnetic waves with a frequency band of 30 GHz to 300 GHz. It is used to measure the distance to an object based on the time difference between when the radio wave is sent from the transmitting antenna to the object, and when reflected and returned to the receiving antenna. Millimeter-wave radar emits radio waves with extremely strong linearity, and is less susceptible to adverse weather conditions such as rain and snow.

The millimeter-wave radar, which is less susceptible to light, is expected to be used as a sensor that complements the functions of cameras and LiDAR

#### It emits laser light such as infrared ray, which hit objects in the front or in the surroundings, and receives the returned light with a light receiver to measure the distance based on the time

Conventional 2D type LiDAR often only measure horizontal surfaces, but the recent advent of the 3D type LiDAR has made it possible to measure multiple horizontal surfaces at once. This makes it possible to distinguish between pedestrians, bicycles and other vehicles, not only because it can measure the distance to the surrounding objects, but also because it enables measurement of an object

Aiming procedure (example)

Mark the position of the vehicle by referring to the maintenance manual.



Paste a specified target on a white board, etc.



Connect the scan tool and perform aiming work

Multi-aiming support tool ADAS MASTER

■ Easy to aim at the vehicle directly with 3 line lasers!
■ Excellent visibility with green line laser!

#### It is possible to aim at the vehicle directly without moving it!

YouTube



By adjusting the panel back and forth, from side to side and the angle of the panel



IM2310-0000


■ Target provided for camera aiming as standard! (Only for domestic vehicles, excluding some vehicles)
■ Equipped with a guide laser for easy sticking of target

Facing the vehicle










**Aiming Support Tool** 

Dr. LINE

Patent pending

Easy positioning of the target reflector during laborious aiming adjustment!

■ With a dedicated laser robot, it is possible to project the light onto the vehicle center line, side line, and orthogonal line specified in the maintenance





■ Ideal for sticking multi-sized targets!




IM2321-0001


■ Board size: 1,400 (W) × 900 (H) (Excluding the stand) Stand depth is 710 mm \* This product does not come with the targets

### **Aiming target**

■ Easy sticking with the magnetic type!



Domestic car-specific target for camera aiming (12 types from 7 manufacturers)




■ Standard target for ADAS MASTER

Target for imported cars (2 types from 3




■ Mercedes Benz · BMW · AUDI



\*This product requires you to prepare camera target, target board, millimeter-wave radar and LiDAR reflector separately (SSST of each car manufacturer)



Target for domestic medium-sized and heavy-duty trucks (5 types from 3 manufacturers)





Millimeter-wave

absorption panel

Ideal for shielding immovable metal objects because it can prevent diffused reflection of millimeter-waves by metal.

IM2325-1000

■ Panel size: 1,065 (W) × 530 (D) × 1,807 (H) mm

#### Millimeter-wave absorption sheet

■ Ideal for shielding floor-mounted objects such as lifts and side-slip testers because it can prevent diffused reflection of millimeter-waves by





Please refer to page 19 for scan tools required for aiming work ▶ ▶ ▶

## Lift and jack

#### Altia Original Small Car Lift

#### Link-type lift

#### Mega Power III/Mega Power Flat Lift

A very popular model that can lift up the vehicles with both boards and arms

■ Altia's original link structure. Can lift up the vehicles with little sway due to vertical rise

■ Equipped with 3-section arms, it can be used for vehicles from light cars to large SUVs and small

At the bottom of the lift, the floor-contacting surface is flat, including the arms! Smooth movement of oil equipment and tool cabinets in and out of the warehouse, providing a sa



Altia's anti-rust lift uses hot-dip galvanizing on the standing board, base frame, and safety claws to reduce rust on the lift caused by snow and snow melting agent adhering around the bottom.



3.2t Board 3-section arm Mega Power Flat Lift

LM8385-F100

ing ■Lifting height: 1,800mm



3.2t Board 3-section arm Mega Power III (Built-in Unit Type)

LM8385-3000



Introduction

Mega Power III (Separate Unit Type)

LM8386-3000

Mega Power III (Built-in Unit Type,

with Rustproof Plating Specification)

LM8387-3000

Link-type lift





#### Ideal for servicing small passenger cars! Basic model of link-type lift

At the bottom of the lift, the floor-contacting surface is flat! Smooth movement of oil equipment and tool cabinets in and out of the warehouse, providing a safe working space

The 3t Slim Slide Board (LM8762-0000) can be added to the pit of the conventional fixed board without additional



LM8766-0000

3t Slide Board Slide Board (Built-in Unit Type)

LM8760-0000

■Lifting height: 1,750 mm

Slim Slide Board Slim Slide Board (Built-in Unit Type)

LM8762-0000

Slide Board (Separate Unit Type)

LM8761-0000

Slide Board (Built-in Unit Type)

LM8766-0000

#### Portable lift **ES Lift**

Ideal for the work with a request that "I want to raise the car a little bit!", such as tire change, body repair, etc. (The maximum lifting height is 870mm)






Electro-hydraulic Type

LM4070-0002

■ Lifting height: 765 mm



■ With the minimum lifting height of 105mm, it is possible to lift up the AERO-equipped vehicle.

2.5t Board Movement OK Air-hydraulic Type

LM4070-1002

■Lifting height: 765 mm

## SKY MAXIII

Gantry 2-post lift/2-post lift with increased rigidity. Equipped with 3-section slide arms as standard.

■ Sturdy construction with 1 cylinder + chain synchronization.

Sky Max III

- Ideal for a wide range of vehicles with different wheelbases thanks to 3-section arm. Easy to set up, even the cars with low vehicle height, due to its excellent usability!
- The High Post Wide can lift such vehicles as Caravan and Hiaces to a high position, allowing even tall mechanics to work with more space.
- Gantry 2-post lift is ideal for plants with ceiling height restrictions, and where many box trucks are warehoused.





The arms of the gantry 2-post lift for car washing adopts the plating treatment!

**Gantry Offset** 

**Gantry Wide** 

4t

LM8333-0000 1,800 mm (1,750 mm for embedded type

ht: 1,800 mm (1,750 mm for embedded type)

Gantry High Post Wide

Gantry High Post Wide (For Car Washing)

LM8334-0000

LM8336-0000 ■Lifting height: 1,800 mm (1,750 mm for embedded type

LM8336-W000

With a wide variety of optional products, it contributes to **■** Options the improvement of workability and plant beautification!



LM8329-0000

■ Lifting height: 1,800 mm (1,750 mm for embedded type)

2-post Lift Offset







2-post Lift Wide

Product LM8332-0000

■ Lifting height: 1,800 mm (1,750 mm for embedded type)



LM8200-0300



► Frame Attachment HA (2 pieces)



LM8200-0400









Speedy attachment

LM8200-1000



**Extension attachment** Product LM8385-0100







attachment LA


















Recharge your phone, tablet, and scan tools! No need to worry about where to put it or where to charge it!



Blue tablet holder for **SKY MAX** 

LM8330-030B

Red tablet holder for **SKY MAX** 

LM8330-030R

## Embedded flat lift Arneo

■ The floor below the lift is flat no matter the lift is lowered or raised, resulting in excellent workability!

■ Enables the cars to be moved in or out of the warehouse smoothly



2-way type



Swing arm type

3t Embedded Flat
2-way slide plate (air type)

Product No. LM5107-KAUJ

3t Embedded FI WNNZ30KA

Product No. LM5107-30KA

3t Embedded Flat
Swing arm (electric)

Product No. LM5108-3WPU

3t Embedded Flat For car wash

Product LM5108-30WP

■Lifting height: 1,790 mm

## Embedded lift Space Lift


■ Achieves efficient chassis repair work



Swing arm type

Plate type













■ Lifting height: 1,700 mm \*\*Space Lift also has the model for car washing.



- With a thin design (minimum height of 105 mm), it can also be installed on floors above the second floor! (Floor type)
- Patented synchro cylinder for reliable hydraulic synchronization!





Product LM4259-00A0

■ Lifting height: 1,800 mm

2.5t Embodde

Z.5t Embedo

LM4259-0PA0

■Lifting height: 1,800 mm

#### Multi Lift

- Flat when it descends to the lowest point, and also flat when it goes up, guaranteeing safe maintenance
- $\blacksquare$  A diverse lineup with or without upper lift and with different board length
- ■With a load capacity of 4 tons, drive-on maintenance of microbuses and the like is possible.



MUS40U

LM4195-0210

Drive-on: 4t
MUS40UF

LM4195-F010

LIMI4195-FU1U

Lifting height: 1,980 mm for drive-on/350 mm for upper deck

### Macross Super Low

Drive-on + freewheel work is possible without pit construction!

■ Realizes a minimum height of 168 mm!

The long standing slopes allows the workers to stand on them smoothly.

■ The unit is separate, so it can be installed on SS \*Embedding is also possible.



Drive-on: 3t

Upper deck: 2t

MUL30E

LM4177-0000

LM4178-0000

■ Lifting height: 350 for upper deck mm/1,600 mm for drive-on

#### 4-post lift Lift Master

A diverse lineup for vehicles from passenger cars to mid-sized trucks and microbuses







For passenger cars and small trucks

For 3t passenger cars and small trucks

MK-300 Standard type

MK-300P Drive-on Panto type LM4326-0000

LM4324-0000



3.5t For passenger cars and small trucks MK-350 Standard type

LM4327-0000

■ Lifting height: 1,700 mm

3.5t For passenger cars and small trucks MK-350D Drive-on type

LM4328-0000

■ Lifting height: 1,700 mm

4.5t For medium/small trucks and micro

MK-450 Standard type

LM4320-0000

■ Lifting height: 1,675 mm

MK-500 Standard type

LM4321-0000

■ Lifting height: 1,675 mm





## ■ Lifting height: 1,700 mm ■ Pantograph lifting height: 340 mm

### Air Garage Jack

MK-300 Drive-on type



## **High Transmission**

Allows 1 person to perform transmission maintenance on vehicles from light vehicles to passenger cars







osition of jack pad: 150mm

through regular inspections.

## **Truck Jack**



1st section: 30t - 2nd section: 15t

BAJ-120W Spec2

Product LM4456-121W

■ Lowest position: 120 mm

BAJ-300 Spec2

LM4556-3001

■Lowest position: 190mm

#### Have you forgotten? Daily inspections! Qualified lift inspectors will carry out safety inspections!

#### • What is the condition of wire ropes and chains?

When was the last time you inspected the wire ropes and chains?

#### • How to check the safety devices?

It is very important to check the operation of safety devices! Raise and lower the lift and check that the safety devices operate properly

#### How is the wear of the rubber pad?

If the rubber pad is worn, the balance of the vehicle body will be lost, which is very dangerous. Replace it periodically.

#### • What is the condition of each bolt and nut?

Are the bolts and nuts on each part of the lift loose?

If the bolts and nuts are loose, the lift will become unstable when it is raised, which is very dangerous. Ensure that tightening is carried out reliably.

※ Certified by Japan Automotive Service Equipment Association

To customers using our lifts

#### Notice of periodic inspection of the lift —


In order to prolong the service life of our products which you have been using on a daily basis, we offer paid inspections by our qualified lift inspectors. For safe usage at all times, in addition to the daily inspection by customers themselves, reliable inspection by a qualified person is indispensable. We recommend early detection of defects through routine inspections and complete maintenance

### What is a "Qualified Lift

This qualification system was established on March 20, 2007 by the Japan Automotive Service Equipment Association for the purpose of properly inspecting automobile maintenance lifts and preventing accidents.

## Lifts for large vehicles

Lifts for large vehicles that emphasize safety and durability





- Accommodates all standard attachments!
- Safe with low-platform type! Reduces the burden on the hands and back associated with moving in and out of the

measures

LM41AD-0000

LM41AD-1000

Are you struggling with setting up the pedestal?

- Working in confined spaces is inefficient and dangerous for workers
- The setting of the pedestal is very heavy work.
- Depending on the tire, it tends to be set easily from an



That struggle will be solved by

safety

pedestal!!

Hydraulic Extension/ Retraction Pedestal (Vertical Storage Type)

16t x 2 posts Twin

LM4142-1RFF

efficiency

5S

LM3032-20CF-S

\*Flat lifts larger than twin lifts can be custom-made according to the specifications of the hydraulic extension/ retraction pedestals.



High work

efficiency



LM4144-0RFF

64t 16t x 4 posts 4 posts

#### **Front Lift**

- Compact design with integrated hydraulic
- Square posts + unique internal structure ensure high safety
- Low oil volume/high pressure type



This image is of a flat type (FLAT&FLAT)

- 13t Cylindrical type (flat type)
- LM4148-0TFF
- Pit type (flat type)
- LM4149-00FF
- 10t Pit type
- LM4130-0001
- Cylindrical type
- LM4130-001T
- ■Capacity: 10t/13t/15t ■Lifting height: 1,000 mm

#### **Medium Pressure Test Lift**

48t 16t x 3 posts 3 posts

LM4143-1RFF

- Test lift that can be selected to suit maintenance and car washing applications
- Floor-mounted and separate hydraulic unit for high




- For maintenance 11t
- LM4120-G000
- For car washing
- LM4120-GW00
- For maintenance
- LM4121-G000
- For car washing
- LM4121-GW00
- ■Lifting height: 1,000 mm



underside washer!

■ Greatly improves car washing

efficiency in combination with the





LM4141-0000

#### Pursuing high work efficiency and ease of use according to the needs of the site!

- ■A lift that raises and lowers the pit floor to achieve safe and fast work.
- ■It can be used for everything from quick work to heavy work, such as oil change and transmission change.

#### A variety of customization and introduction cases




Floor Lift

Safe simultaneous work is possible on the front and rear of small and medium-sized vehiclesis!

▶Pit lift




►Stairs + slide covers



▶Panels for avoiding falling into the pit

Lightweight panels for easy opening and closing
 Can be installed to existing pit openings



►Oil drip pan

High work

efficiency

▶ Customized parts of the lift (optional)



Please store it inside

**Improved** 

safety

Maintenance system of large vehicles

#### Quick Service Trio

Various responses to quick maintenance and heavy maintenance with the combination of floor lift + axle

- ■Achieve efficient and safe work for low-floor vehicles, non-step buses, etc.
- ■Upper and lower simultaneous maintenance is possible, that is performing maintenance from above by holding the axle lift and from below by lowering the floor lift.



7m specification

LM4190-1010

12m specification

LM4190-1020



►Safety equipment (optional)



LED light Fixed



Reel

▶Transmission lift (optional)

Oil server

The Quick Service Trio can be combined with customized floor lifts for more efficient maintenance.



surface, and effective use of the work space can be achieved



■ 4 units/set

.M4348-0000

■Low profile: 295 mm (body height)

#### **Frame Lift Series**

Combined with the front lift to increase efficiency!



10t Rear insertion type

Big 10

LM4353-0000

■Lifting height: 510 mm

**Big 15** roduct No. LM4354-0000

■Lifting height: 470 mm

### Low-profile type

### **Truck Lift Series**

Allows for smooth movement!



LM4357-1000

LM4357-1500

■Lifting height: 600 mm ■Lifting height: 600 mm ■Low profile: 300 mm (body height)

## Vehicle washing

We back up a wide range of car washing businesses, such as daily car washing, manual car washing and interior

#### Leave the body and chassis washing to the high pressure washer!

HP 000

High pressure hot water washer

#### Mega Shine

Fuel-efficient, lightweight and compact! Eco-friendly high pressure hot water washer

Eco1200-II Deluxe Type CS7112-10DX

Eco1200-II Standard Type

CS7112-10ST

■Flow rate: 900 L/h ■Pressure: 11 MPa

For medium-sized vehicles

1300 HP (50 Hz) CS7113-0000

Product No. CS7115-0000

1500 (60 Hz) CS7115-6000

1300 HP (60 Hz)

CS7113-6000

- ■Flow rate: 1.000 L/h (1300 HP)/1.500 L/h (1500)
- ■Pressure: 11 MPa (1300 HP)/9 MPa (1500)

#### For large

1500 (50 Hz)

2000 (50Hz)

CS7020-0000

Product No. CS7020-6000

2000 (60Hz)

3000 (50 Hz) CS6030-0000

CS6030-6000

■Flow rate: 1,650 L/h (2000)/2,050 L/h (3000)

3000 (60 Hz)

Aguashine



1200

CS7001-0000

■Flow rate: 900 L/h ■Pressure: 11 MPa



for underside washing!

High pressure cold water washer

3000GIGA (50 Hz)

CS7003-0000

3000GIGA (60 Hz)

nprove

efficiency

CS7003-6000 ■Flow rate: 2,110 L/h ■Pressure: 6 - 7 MPa



Multi-functional car washer to support high value-added car washing!

High pressure hot water foam car washer

#### Power Fall AW-01H

With high-pressure water + high-pressure detergent + foam + water expulsion + hot-water washing, multi-functional washing is possible with just one unit



Standard painting Product No. CS6251-00H2



Hand Blow BL-11-L

■ Cumbersome water wiping work is greatly improved by a powerful blow



Labor-saving wiping after car washing!

#### Ideal for new value-added cleaning!

#### **HOT-FOAM SW-15**


■ Cleaning with fine mousse allows everyone to deliver uniform and stable cleaning results



It can be used in conjunction with a gantry car washer! It effectively cleans dirt and snow melting agents from the chassis!

#### Automatic underside cleaning device

 Automatic washing of the chassis is possible without moving the vehicle!



CS9002-0001

CS9004-0000

#### Fixed underside washer


■ Helps to significantly reduce working time and labor required for chassis cleaning compared to manual car washing!

■ Powerful cleaning, effective for cleaning potassium chloride and mud



underside cleaning!

A separate high-pressure washer is required to the introduction of the underside washer Depending on the washing environment, it may be necessary to introduce multiple highpressure washers.



CS9003-0000



Aguashine 300 GIGA

for satisfactory cleaning effect!



JR-65 For large vehicles

CS9001-0000

15

Vehicle washing equipment

#### **Gantry car washer**

#### **KINO**

- Footprint is 4m x 8m, achieving space-saving
- installation
   Equipped with "X-style control" that uses 3 brushes for cleaning! Enhanced power to clean upper and lower parts of the side of the vehicle and areas near the side mirrors



CS6678-0000

#### **Zekus**

- Footprint is 4m x 8m, achieving space-saving installation
- First of its kind in the industry! Equipped with front side brush!



CS6681-0000

#### NewT-X II

 Able to handle car length of up to 5.200 mm. and can wash large one-box cars such as Hiace!



#### **Dispect III**

 Achieves high cleaning power with a total of 5 brushes





CS6629-001M

■Machel specification

#### KABUTO II

Achieves high-quality and profitable car washing with an option-rich car washing menu!



CS6676-0000

#### **Magic Through**

High-speed washing of cars contributes to the revenue of the stores that have introduced this



\* The continuous car washer Magic Through is available on special order

#### KAI

- Achieves an overwhelming reduction in the
- burden of washing the large vehicles!

  Comes with diverse options such as cold weather specification and water-repellent coat





CS6607-0000

#### Camion Custom

- 4 minutes per car, the fastest car washing in the industry! (When washing a 10t car/12m body back and forth for one round)
- Operability, safety and cleaning power have been further enhanced!



CS6680-0000


Powerful cleaning of the objects to be cleaned with high power!

#### Keep your plant floor clean and tidy!

#### Parts washer



**JW-200PB II** 



Maximum size/weight of washing target: Φ630xH300mm/100kg



CS6320-080C

Maximum size/weight of washing target:  $\Phi$ 800×H400mm/120kg

#### Floor scrubber




Vispa xs Scrubber

CS6958-0000

Easy-tooperate selfpropelled type

Antea 50 BT (self-



ompact tyr that achieves strong cleaning power

**Automatic Floor Scrubber** 

EG-3a

#### A highly effective cleaning tool that thoroughly cleans every corner of your car!

"Sukkiri Clean" with a dust collector, for cleaning the inside of the car in a short time

















- \* The manual, manual DVD, and sales promotion data are included only when you purchase "Sukkiri Clean" It is not included in the single product

### Chassis equipment

If you are aiming for labor-saving and reliable maintenance, our latest equipment is your first choice!

#### Tire changer **Smart Winning Series**

Applicable maximum rim diameter is 24 inches

Supports rim diameter of up to 22 inches, except for RSW-06EZ

Mount press



Bead press

Altia original tire changer that allows you to choose from various functions and equipment variations

Equipment	list	(RSW	series)	į

Equipinioni list	(11011 30110	,3)					—	
Model	RSW-06EZ	RSW-05EZ	RSW-03	RSW-02	RSW-01M	RSW-01	RSW-00	RSW-21
Bead press	•	•	•	•	_	•	_	_
Mount press	•	•	•	•	_	_	_	_
Inflator	•	•	•	_	Δ	Δ	Δ	Δ
Compact press	_	_	_	_	•	_	_	_
Leverless device	•	•	_	_	_	_	_	_

Standard equipment △Optional - Not equipped

Model	RSW-06EZ	RSW-05EZ	RSW-03	RSW-02	RSW-01M	RSW-01	RSW-00	RSW-21
Bead press	•	•	•	•	_	•		_
Mount press	•	•	•	•	_	ı	ı	ı
Inflator	•	•	•	_	Δ	Δ	Δ	Δ
Compact press	_	_	-	_	•	-	-	-
Leverless device	•	•	ı	_	_			_
				-				

#### **RSW-06EZ**

**RSW-05EZ** 

Product	WS3299-06ET
No	**************************************

WS3299-606M

RSW-01M

**RSW-01** 

WS3299-6006

**RSW-03** 

WS3299-8006

WS3299-06ER

**RSW-00** 

WS3299-5006


**RSW-02 RSW-21** 

WS3299-7006

WS3299-4006

■Applicable rim diameter: 10 to 22 inches (RSW-06EZ only supports 12 to 24 inches)

3.5 - 13 inches (RSW-21 only supports 3.5 - 11 inches)



The standard equipment has been upgraded to make it even easier to use!

#### ■ Vertical arm cover [all models]

For preventing dirt from adhering to the vertical arm and improving safety during




#### ■ Tire cream container [all models]

Equipped with a tire cream container that is indispensable when changing tires, contributing to improved workability.

\*Tire cream is not included

■ Independent operation of upper and lower rollers of bead press



Work is now possible without the bead press interfering with the tire.







### Wheel balancer

### **Smart Load Series**



Applicable maximum rim diameter is 30 inches

In the case of manual operation



🍒 RSR-X

<ul> <li>Standard equipment △Optional - Not equipped</li> </ul>
---

Equipment list (NSK series)	Colandard equipment Zoptional Not equipped							
Model	RSR-LA, R	SR-X, RSR-S	RSR-V	RSR-H				
Automatic input system	Distance and rim diameter			Distance	Distance			
Aluminum auto system	•	•	_	_	_			
忌 Simple input system	-	•	•	•	•			
Auto position search	•	•	_	_	_			
g WAS system	•	•	•	•	_			
ELED lighting device	•	Δ	Δ	Δ	Δ			
Laser sensor - fully automatic input	•	_	_	_	_			
Automatic rim width input	•	_	Δ	_	ı			
Fine mode switch	•	•	•	•	•			



WS3210-L000

■ Applicable rim: 10-26 inches in diameter/2-15 inches in width For manual input of the entire lineup Applicable rim: 10 - 30 inches in diameter

#### **RSR-S**

WS3210-S000

■ Applicable rim: 10-20 inches in diameter/2-15 inches in width **RSR-V** 

#### WS3210-V000

■ Applicable rim: 10-20 inches in diameter/2-15

es in width
R-H
Hand spin type RSR-H WS3210-H000

■ Applicable rim: 10-22 inches in diameter/2-15 inches in width



RSR-LA

#### **RSR-X**

WS3210-X000 Applicable rim: 10-26 inches in

diameter/2-15 inches in width

#### We can also replace and balance tires of large vehicles!

#### Tire changer Mega Wining II

- Ideal for replacement of tubeless tires!
- Double action method to speed up work!



TB LT Tubeless

#### Product No. WS3955-1000

- ■Applicable rim diameter: 16 22.5 inches
  ■Maximum tire diameter: 1,100 mm
- ■Maximum tire width: 300mm

### Tire changer

- Top model comes with
- Also applicable to ultra-flat tires!



Product No. WS3316-0000

#### Tire changer Giga Wining

- Achieves fast and comfortable changing
- Double action method to speed up work!



OR TB LT AG Tubeless

- Product No. WS3303-0000
- ■Applicable rim diameter: 16 35 inches (with extension bar mounted: 35 - 52 inches)
- ■Maximum tire diameter: 2,400 mm
- ■Maximum tire width: 1.250 mm

#### Wheel balancer Mega Road II

From passenger cars and large vehicles, this one unit covers all your balancing needs!



TB LT (optional) PC (optional)

Product WS3197-2000

- ■Applicable rim: 10-30 inches in diameter/2-20 inches in width
  ■Measurable weight: Up to 150 kg

## **Exceed XX**

various specifications



- ■Applicable rim diameter: 10 26 inches (10-22 inches/12-22 inches/14-26 inches)
- ■Applicable rim width: 3.5 14 inches

### **Corno Tire Changer**

■ Standard model (5020TI) for a wide range of needs

> \* This image shows the 5020TI-2S equipped with options.

5020TI-2S (2-speed specification)

WS4600-0000 5020TI-B (explosion-proof

specification) Product No. WS4600-1000

■ 5020TI: Applicable rim: 10-20 inches in diameter/4-13 inches in width

5024TI-2S (2-speed specification)

WS4600-4000

5024TI-B (explosion-proof specification)

WS4600-5000

■ 5024TI: Applicable rim: 10-22 inches or 12-24 inches in diameter (select when ordering) /4-14 inches in width

### **Corno Wheel Balancer**

■ Measurement time is 5 seconds! Laser line as standard equipment



9015W (explosion-proof pecification)

WS4702-0000

For reducing the impact of bursting when the tire is filled with air, contributing to improved safety!

#### Safety enclosure for air filling Mega Safety II

Have you taken safety measures when filling tires with air?

Under the Occupational Safety and Health Act, businesses are required to use equipment such as safety enclosures to prevent burst tires from flying towards the workers



WS3198-2100

Single-row type: Automatic air

WS3198-2100

Double-row type: Automatic air filling

Product WS3198-2200

opening width

■Applicable tire diameter: 1 200 mm ■Applicable tire width: Within 560 mm A labor-saving item that is indispensable for chassis maintenance! Ideal for improving work efficiency and dealing with labor shortages!

#### Wheel Dolly



Mobile NWD-500G

WS4050-0000

Rail type

WS4055-0000

### **Tatteler**



Product No. WS4065-0000

#### **Tire Dolly**

- Reduces the burden of 4 actions: picking up, transporting, putting down and unloading! ■ Four tires of Φ530 (light
- vehicle) to Φ820 (RV) can be transported at the same time!





NTP-217B (Standard Type)

Product WS4053-0000

#### **Power Torque Setter**

■ Built-in electronic control controller enables advanced tightening torque management



**PTS-800E** 



Set torque range: 400 - 800 N (10 N·m step) ■Air usage: 0.56m³/min
 ■Body weight: 11.8kg (without socket)

#### **Large Impact Wrench Hoist** Leg Car

- Even a large, heavy impact wrench can be operated upward, downward, leftward and rightward with light force
- Safe and quick installation and removal of tires for large vehicles



NRH-618

Product No. WS3741-0000

NRH-618H (Standing Type)

WS3742-0000

#### **Brake Disc Grinder**

■ Equipped with automatic runnerout correction rotor matching system!



WS3002-1000 ■Applicable disc diameter: 120-380mm ■Applicable disc thickness: 5 - 40 mm

PFM 9.2DRO



■Applicable disc diameter: 102-420mm ■Applicable disc thickness: 5 - 40 mm

## Scan tools and battery-related

EGLIN DENI Canetance, and battery and EV-related maintenance with the latest tools!

#### Android tablet-based scan tools SSS-T2 Series

Powerful support for the diagnosis business with a scan tool that "shows diagnostic data" and "proposes suggestions " to car

- ■Reduction of vehicle information input by reading the QR code of vehicle inspection
- ■Not only domestic cars, but also imported cars are well diagnosed! (Imported car unit)
- ■10.3-inch tablet for easy viewing of data monitor and graphs
- ■Cordless diagnosis improves work efficiency! SSS-T2+ (a full set: SSS-T2 and

dedicated model for imported cars)

EG3005-5000

Product EG3005-0000

Dedicated SSS-T2 for imported car

Product No. EG3005-SC00

Scan tools for specific maintenance

Supports all 23 manufacturers!

Vehicle data updates after purchase

Free for 3 years'

Repair consultation hotline

Free for 1 year

X Data updates of imported cars are free for one year (all 54) manufacturers included)

#### Improved function

Reads the QR code of vehicle inspection certificate to get the vehicle information! Reduces the troublesome vehicle information input for improved workability. It also prevents human errors such as wrong selection.

#### Improved function

It is possible to adjust the optical axis of the front recognition camera of ASV (advanced safety vehicle) and to adjust the aiming of millimeter-wave radar.

Some car models and vehicles are not supported.



#### Tire, battery and oil change mode (TBO mode)

The complex registration and data clearing usually carried out in brake oil bleeding mode, idling-stop vehicle battery replacement mode, AT/CVT oil/tire replacement mode, etc. now can be performed through a series of operations in this epoch-making mode.

An

#### Tire

Sensor registration after change and rotation of summer/winter tires of vehicles equipped with **TPMS** 



#### Battery

Judgment on the necessity of vehicle battery replacement, and clearing of data on cumulative current after replacement



Service lamp reset after engine oil change, oil temperature check before AT/CVT oil change removal of air from electric oil pump after oil change and clearing of deterioration data



#### Vehicle inspection and maintenance

Confirmation of the amount of refrigerant charged in air conditioner, air bleeding when replacing cooling water in HVs, air bleeding of brake fluid, switchover to maintenance mode,



PC and scan tool cart

GW9507-0000

#### Vehicle health checkup

You can perform a vehicle health check and print a diagnostic report with your Wi-Fi printer.

In addition, by reading the QR code of the vehicle inspection certificate with the built-in camera, you can save the effort of entering vehicle information.

#### SSS-a II

 Multipurpose, ideal for diagnosis and aiming of domestic passenger cars, domestic trucks and imported cars!



EG3004-0000

What can be done with SSS-qll?

- Diagnosis · Active test · Data display
- · Work support · Freeze frame
- Customization

## Free for 2 year

■Nissan car battery change screen



Android tablet-based scan tools

#### Scan Pad

■ Supports the diagnosis of vehicles from more than 100 vehicle manufacturers, including domestic and imported vehicles



Free for 3 year

Free for 1 year

EG3201-0000



#### Automatic quick charger





HR-MAX70D

**Brain Max BR-MAX70iS** 

BS6602-0000

**HR-MAX70D** (Silicon Type)

BS6591-070D

Battery system analyzer

Charge display in percentage - You can

BS6608-1000

manage everything from numerical SOC,

battery starting and charging, to customer

AA1000RP

management, on your computer

#### Pro booster **DSR132**

For gasoline cars of up to 8000CC and diesel cars of up to 5000CC!

**INC-100J** 

**Battery charger and** power supply

during customization and aiming!

■ Powerful backup of up to 100A is possible

Great for exhibitions and events due to its

size that can be stored under the car

Reprogramming voltage can be set at

BS6534-0000

13 to 14.8V



BS6609-2000

■ For 12V cars only ■ Maximum output: 1200A

### **CTEK** battery charger

- For the batteries of charge-controlled vehicles, idling-stop vehicles and auxiliary equipment!
- Also possible to charge the battery in an idling state for a long time during aiming operation!





BS6530-7000

BS6535-0000

MXS7.0JP



BS6530-7000

■For 12V lead battery

PRO25SEJP



BS6535-0000

■Compatible with 12V lead/lithium

### Start booster

■ Resistant to deterioration, and capable of charging and discharging for 1 million times!



C1-TR-1224V

BS6667-0000

C10-12V (for 12V cars only)

BS6666-0000

■ Maximum output: 3,500 A

C15-24V (for 24V cars only)

■ Maximum output: 4.500 A

BS6667-0000

BS6668-0000

PRO25SEJP (for 12V/24V cars)

■ Maximum output: 20,000A for 12V cars and 10,000A fro 24V cars

### Have you taken measures to maintain your EV?

We are pursuing a policy of decarbonization that does not rely on limited petroleum energy in various industries and industries in consideration of the global environment, CO2 reduction, and global warming. In the automobile industry, the popularization of EVs (electric vehicles) that do not rely on gasoline or petroleum is accelerating, mainly in Europe, and domestic car manufacturers have set targets for their introduction.

In the future, with the popularization of EVs (electric vehicles), the maintenance environment of the automobile aftermarket will also change dramatically, and each maintenance plant will need to introduce new equipment to match the times, such as insulation tools and special equipment to prevent electric shock and damage.

**Stacker** 

Effectively transports EV batteries.

#### Insulating tools



KLIN-27-SELB

Product No. HT2000-2000

Product No. HT2000-4000

※ In order to use insulating tools safely, it is necessary to set an expiration date of 3 years from the date of purchase, and once-a-yea inspections are required for continued use

#### Module balancer

For adjusting the balance of the EV battery cells



X The product image is for

Supports safe EV battery maintenance.



Electric table lifter



X The product image is for illustrative purpose only.

#### Airtightness tester

For measuring the airtightness of the EV batteries



\* The product image is for illustrative purpose only

#### **Quick charger**



Product BS6800-0000

#### **Battery charging and** discharging machine

For efficient charging and discharging of EV batteries.



illustrative purpose only

X The product image is for illustrative purpose only.



#### EV/PHEV charging items



X The image of the Product No. GW8870 charging cable is for illustrative purpose only

## Labor-saving and efficiency-improving equipment

A lineup of labor-saving items that are essential for the times to come!

Dedicated equipment is required for safe and sound gas recovery and regeneration of HFO-1234yf (R-1234yf)!

#### Air conditioner gas recovery/regeneration equipment

- For three applications: cleaning, gas recovery, and gas charging.
- Equipped with a large-capacity dry filter and a powerful vacuum pump for basic
- Suitable for hybrid vehicles and EVs



For R-134a and R-1234yf

EE6427-5000

 Automatic metering and filling of gas, oil and fluorescent agent!

■ Equipped with automatic flushing system!

Equipped with an automatic air



EE6415-2000

■ 2-cylinder specification

■ Fully automatic air conditioner service, such as recovery, regeneration, vacuuming, and refilling, is made possible with just one machine!



For R-134a and R-1234yf

OKC-DUAL-PT (with printer)

EE6416-2001

#### Gas charger Manifold gage set

■ Adopts liquid return method (PAT)! Prevents refrigerant discharge loss and quantitative filling



CP-2VS-YFE (for POE oil)

EE6431-1000

CP-2VS-YFG (for PAG oil)

EE6431-0000

We support oil changes with a wide variety of items that meet the needs of electric operation, draining from above, and draining from below!

#### Oil changer



MO-D12 (rechargeable and

LS6018-0000



T-75N (electric, draining

LS5467-0002

■Tank capacity: 70L

#### Oil drain



■Tank capacity: 55L

LS5420-100R



LS6016-100R

■Tank capacity: 80L







**Drain cart** 

LS6016-6000

#### **Fully Automatic ATF/CVTF Changer**

Increased efficiency and profitability with fully automatic ATF changer!

For hybrid

Compatible with level gage

CLIMAX AMC-1000

LS6000-1000

CLIMAX AMC-1000 (with printer)

LS6000-100P

AFC-3000TF

Product LS5104-0000



LS5104-0000



#### **Brake Fluid Changer** High Bleeder BB-1000RN

■ Compatible with various advanced brake systems Supports streamlining of services from light to large vehicles

> Compatible with light to



WS3376-10RS

■Dimensions: 450 (W) x 490 (D) x 920mm (H)

#### **Engine Auto Refresher**

■ Removes the semi-solid sludge and carbon attached to the engine oil lines without disassembly work, and restores the performance to that of a



EG1916-0000

#### **DPF Quick Refresher II**

#### A major revolution in DPF maintenance!

- Powerfully cleans the PM and ash in the DPF using a dedicated machine!
- The DPF can be cleaned while on board the vehicle! No need to remove it.



EE5001-0000

EE5000-2000

(Sold separately) Initially introduced chemical set (for about 3 units)

Contributes to reducing DPF cleaning time and improving fuel efficiency!





Conventional DPF removal/

Working time Manual washing **About 5 hours** 

**DPF Quick Refresher II** 

**Automatic** Nozzle set washing

\* The working time of both processes includes forced combustion with a diagnostic machine

#### YouTube 500,000km driven. The number of forced burns has increased..

Watch the product video here



### SOS signal of DPF!

- Poor fuel economy
- •Engine does not emit exhaust
- Power has been lost.

4.9kPa

- Forced combustion of **DPF** is common
- •Black smoke or white smoke is emitted



Removal and cleaning is also automated with the off-thecar attachment!

**Wireless Noise Catcher** 

■ With the installation of dedicated software, it is possible to

Excellent usability with wireless communication!

M size (φ185mm)

EE5001-4000

L size (o268mm)

EE5001-5000



#### Reel

Air Hose Reel SHS-210A

CM6923-0000

L Edge Light Reel

GW9193-6000

Remote Control Reel SPS-308A

GW9153-0000



CM6923-0000

installation

Slow Motion Air Reel SHS-210ASLOW

CM6923-000

working environment due to slow rollback!


**About 3 hours** 

EE6312-0000

Exhaust Hose Reel S3-5SNR









In addition to air reels, there are many other lineups such as cord reels and switch reels

#### Spot and zone air conditioning system **FLEX AIR**

 Achieves spot air conditioning and zone air conditioning even in buildings such as factories and warehouses where overall air conditioning is difficult due to no partitions and high ceilings!

■ The air conditioner can be applied to the targeted area, so you can deliver cool winds to each person!

■ Individual operation possible! Ideal for reducing power waste!







Fully air-condition where you

The wind speed is high, so it feels like a draft.
You can feel the cool breeze!

#### **Assist Vest "TASCHEL"**

■ It assists posture without power, reducing back pain caused by lifting heavy objects or staying in the same posture for a long time!



AW0200 ■Size: S · M · L · LL · 3L

#### Package-type Air compressor

■ The soundproof and vibrationproof design contributes to the improvement of the working environment!



NLP-W-37P/ NLP-W-37PRD (with air dryer)

CM7120

- ■50Hz/60Hz
- ■Rated output: 3.7kW









We accept orders ranging from total solutions for EV charging spots to construction of various road markings. Please contact our representatives for de

## **Body repairing and painting**

equal bhe high-strength steel sheets, water-based paints, and new materials?

#### **Push-pull Painting Booth**

#### Lineup for passenger vehicles

#### ►CAB-08

- Highest specification in pursuit of high performance and convenience
- Achieves a "uniform and soft flow of air" with the new exhaust and supply unit



### ►Max • Convert • Advance Wide MC-201WH

 Next-generation painting booth with excellent operability and spacious space



#### ►CUBIC LGS-4073

- Hot air as standard for drying waterbased paints!
- Excellent workability in a spacious space!



#### **►**CX07

New standard model with operation touch panel



#### Lineup for large vehicles

#### ►CAB-747

■Significant reductions in fuel consumption, power consumption, and maintenance costs are possible



**▶**G-MAX

\* The image is of a shutter-type booth (optional)

■Creates a spacious and bright work space



#### ▶CUBIC LGS-5016

 With push-pull and heat-circulation functions, it improves productivity and provides a high-quality painting environment



#### Aerial work equipment

#### PICK UP!

It is recommended to introduce aerial work equipment that achieves a high degree of safety when painting large vehicles.

▶ Image of Cubic series LGS-BB-LT-XYZ Pneumatic Access 3D lift (a type that can move back and forth, left and right, up and down)



Compact storage at the end of work!





We have a large lineup of painting booths, depending on guide dimensions, heat source (presence or absence and type of fuel), installation method (floor type, pit type), etc. 
Please contact our representatives for details.

### Simple Painting Booth

#### ▶ Space Booth Advance New SPB-42

■ Makes the most of limited scarce!



Space Booth Advance New

#### ►Merit III

For

passenger

cars

- Accordion type, with sturdy structure
- Two lineups are available: standard type and high roof type.



Simple painting booth Benefits III

#### **▶**Merit Grand

■ Achieves effective use of space



For large vehicles

30 H

#### Dry exhaust system

#### **Matching Master**

- Pre-filter with high dust-retention capacity prolongs the filter replacement interval
- Double filtration by pre-filter and main filter for superior repair efficiency



KH-4N

#### **Hot Air Painting Machine**

■ Top-class model with the highest power in its class and a noise reduction function



SG2500

BP7220-2500

#### Dedicated hot-air dryer for painting booths **Mighty Junior**

■ It can also be installed in existing booths!

Time for hot air to rise to 40°C About 10 seconds

Drying time as compared to blower operation time Approx. 1/3

Power consumption in a standby mode as compared to that in an operation mode

Approx. 1/10



Painting dryer

#### **Heatup Plus**

A wide-ranging lineup, including nearinfrared clear lamps, and carbon lamps for water-based paints.

#### 1-light mid-infrared lamp HUNM-1

BP7384-1M00

Applicable to water-based paints

#### 3-light carbon fiber lamp HUNK-33-D

BP7384-3K00



HUNM-1



Hanging type

Mobile hot air generator

#### Two-light Black Carbon Heater


Quiet! Compact! Easy to use for drying in any situation!



BP6502-0000

#### Carbon Hand Heater

- Touch-up drying of water-based paints is made faster with the near-infrared rays + far-infrared rays!
- Workability is further improved with a dedicated hot air kit! (Optional)



CH-600

BP6500-0200

#### Film Thickness Gage

- Vehicle coating and plating thickness can be measured
- Supports measurement of ferrous and nonmetallic substrates



**TG-02U** 

BP7199-1000

#### **Toning Light**

- Cordless design for excellent workability!!
- Illuminance is adjustable to 2700 lux/10000 lux.



Day Light 216

BP7303-1000

### **Sample Panel Dryer**

Accurately determines the hue of tone with forced drying!

■ Color change due to drying and hardener reaction can be checked in a short time

> Also applicable to ater-based paints!



BP6501-0000

### Spray Gun Cleaner

- Speedy cleaning is possible with the power of ultrasonic wave + heat + vegetable detergent! Whether it is water-based or solvent-based paint, one machine
- can deal with both!



Spray Gun Cleaner ECO







■ Due to its compact size, it can be installed in convenient locations such as the wall of the painting booth or near the painting workshop!







UM80, for water-based paints (wall mounted)

**BP9303-080W** 

#### **Thinner** Regenerator

■ Contributes to improving the working environment by preventing an increase in storage space for dirty solvents and waste disposal costs!



#### **URS600CE-SJ**

BP9300-601S

**URS700SSJ** (stainless steel)





#### Ultrasonic 3D alignment measuring system

#### SHARK 3

- Simple, accurate and simultaneous body measurements at up to eight locations!
- Due to the ultrasonic technology, the position can be accurately determined by picking up ultrasonic waves from the probe set at the measurement point, and real-time measurement is possible!



#### 3D multi-alignment measuring system

#### TOUCH

- Freely maneuverable even in narrow spaces, regardless of work environment
- Free measurement of the under and upper bodies
- The measurement data can be printed out and attached to the warranty card.





## Jig bench-type frame correction machine Enjoy Bench

### ■ It is possible to measure and adjust body alignment with

high precision!

Achieves a comfortable working environment with a lifting height of 1,500 mm!



#### **Frame Correction Machine**

#### ▶Body Repair Set

#### ..,

**BR200** 

# TO THE

**▶**Body Restore Set




BR300

Product

BP7546-0119

#### **▶**Body Complete Set



Top-of-the-line model that combines floor rails, cubic lifts and a variety of tools

#### BR500

Product No.

BP7546-0305

\* The images are examples of the introduction of floor rails and cubic lifts

### ► Truck Frame Correction Machine



\* The truck frame correction machine (rail type)
can be made to order

### **Plastic Welder**

BP7546-0120

- Crack, chip, and tear of plastic exterior parts (bumpers, etc.) can be welded easily, quickly, and with high strength!
   It is possible to repair damaged bumpers
- It is possible to repair damaged bumpers due to hail and ice on the road surface, and damaged bumpers and headlight tabs due to the impact of accidents!

#### Repairable targets (one example)

- · Bumper · Headlight tab · Washer bottle · Overflow bottle · Fan shroud
- · Fender liner · Rocker panel molding · Fuse box · Air box
- Battery box Undercover Motorcycle fairing ATF fender





#### Repair case

#### Repair of damaged bumper tab

#### BEFORE








Repair of bumper crack

#### BEFORE

AFTER



\* The image shows the condition before painting

Apart from plastic parts, welding is also possible for other parts!

\*\* Limited to plastic material.



**Plastic Welding Kit** 

PRODUCT BP8054-1300

### Multiple solutions for various shapes and





**Airless Plastic Welder** 

Product BP8054-1000



Nitrogen Plastic Welder With Digital Nitrogen Generator



BP8054-0000

## **Welding Fume Exhaust**

#### PICK UP

Welding fumes have been designated as specified chemicals in the Ordinance on Prevention of Hazards Due to Specified Chemical Substances, and the employer has been required to take measures such as introducing ventilation equipment and using protective equipment for workers. (Enforced and applied from April 1, 2021)





Usage image

#### Stud Welder

- This unit can be used for pressing and welding the washers onto hightensile steel plates!
- Blows out air for forced cooling when warmed up after power-on. Minimizes distortion.



**Best Handman SKE-7000** 

BP8006-7000

■ Single-sided welding is possible for iron plates and stainless steel plates of no more than 0.5 mm in thickness!

 Realizes continuous spot welding (seam welding) with the rolling tip!





SW-3700

BP8052-0000

#### Wonder Welder **YS50Q**

BP7975-0001

#### Spot Welder

BP8055-0106

FBM-105 (50 Hz)

FBM-105 (60 Hz)

A high-class model that combines performance and workability



ALPHA V

BP8044-0000



**MONSTER S-1001M** 

■Maximum output: 12,500 A

BP8040-0000

■Maximum applied pressure: 750 kgf

■ Affordable model for high-strength steel plates

KNIGHT (water-cooled)

■Maximum current value: 10,500A

■Maximum applied pressure: 350 kg

BP8043-000W

■ Washer welding is also possible!



■ Equipped with

performance as

that of those on

the production lines of car manufacturers

the same

YSI-24EZ-C



■Maximum output: 11,000 A ■Maximum applied pressure: 400 daN



**Plasma Cutter** 



BP7950-9105

KITTER II

BP8019-1000

#### **Semi-automatic Welder**

■ Lightweight! Compact! Outstanding cost performance!

■ Equipped with synergy (unified control) dial and Mild ATC function!



■ Inverter control allows anyone to perform stable welding work

 Also very useful in general maintenance such as muffler welding!

Mig Box M-180

 Dedicated stand as standard



 Can be used anywhere with a built-in device for preventing electric shock!

Semi-automatic welding, manual welding, and TIG (optional) welding are possible!



AW-185

BP8056-0000

#### ■ Stable welding that is not affected by hand tremble is possible by keeping changes in current and voltage constant

 Ideal for gap welding and tack welding. especially the repair welding for body panels! (Interval welding function)

#### Uni Auto 160BF

BP7857-0001

#### IH- dent repair system **T-Hotbox**

BP7954-6000

■ Lightweight and compact, the process from setting to repair can be completed in short time!





BP8800-0000

#### Aluminum dent repair Alu T-Hotbox

BP8010-5000

■ Can be used to repair panels made of any aluminum alloys

easily repaired!



BP8801-0000

### **Dent Lifter Kit**

■ Easy repair of small dents



BP3500-6000

#### Wind repair system ecoVacs Mini Plus **Complete Kit**

Ideal for repairing damage to automobile glass caused by flying stones, etc.!

Easy operation and short work time contribute to great profits!

Achieves shorter work time through a simple process! BEFORE






BP8802-0000

26

## Aiming to eliminate accidents related to maintenance equipment.....

#### Let's prevent accidents due to non-performance of inspections!







Inspection points

- Confirmation of wire rope and chain
   Confirmation of lubrication around each pin and rollers
   Confirmation of safety devices

- Confirmation of oil change and leakage
   Confirmation of wear of rubber pad
   Confirmation of abnormal noise and vibration

~To customers using our lifts~ Would you like to have your lift checked regularly?

In order to prolong the service life of our products, which you have been using on a daily basis, we offer paid inspections by our qualified lift inspectors. For safe usage at all times, in addition to the daily inspection by customers themselves, reliable inspection by a qualified person is indispensable. We recommend early detection of defects through routine inspections and complete maintenance through

What is a "Qualified Lift Inspector"?

This qualification system was established on March 20, 2007 by the Japan Automotive Service
Equipment Association for the purpose of properly
inspecting automobile maintenance lifts and
preventing accidents.

#### **ALTIA Japan Service Network**

We have deployed Service Stations (NSS) throughout the country, with our branches serving as key stations We have a perfect service support system in place

### Sapporo Branch

NSS Kitami NSS Asahikawa NSS Asahikawa Cente NSS Obihiro NSS Kushiro NSS Sappord NSS Sapporo Higash

NSS Muroran

NSS Hakodate

#### Sendai Branch

NSS Hirosaki NSS Tokuwada NSS Akita NSS Morioka NSS Hokuiou NSS Osaki NSS Sendai NSS Nagase NSS Date

NSS Yamagata Cente NSS Fukushima NSS Iwaki

NSS Komachi

#### Metropolitan Area Branc

NSS Saitama North NSS Kohoku NSS Saitama East NSS Shin-Yokohama NSS Saitama South NSS Sagami NSS Tokorozawa NSS Yamanashi NSS Saikyo NSS Kawaguchi NSS Chiba

NSS Keiyou NSS Jounan

NSS Jousa NSS Keihin

#### Kanetsu Branch

NSS Iharaki NSS North Kanto NSS East Niigata NSS Chuetsu NSS Nagano

NSS Nagano Cente NSS Higashinagano NSS Matsumoto NSS Ueda

#### Nagoya Branch

NSS Ise NSS Shizuoka

NSS Enshuu

NSS Tovama NSS Shiga NSS Ishikawa NSS Uii NSS Higashi Osaka NSS Hamamatsu NSS Yao NSS Nagoya NSS Hirakata

NSS Gifu NSS Hyogo NSS Nishinomiya NSS Tajimi NSS Higashinono NSS Kishu NSS Hanshin NSS Mie NSS Hannah NSS Yokkaich

#### Osaka Branch Hiroshima Branch

NSS Shimane NSS Shikoku

NSS Takamatsu NSS Tyugoku East NSS

#### Fukuoka Branch

NSS Western Japan

NSS Fukuoka Center NSS Saga

NSS Nagasaki NSS Higashi Kumamot

NSS Oita

NSS Miyazaki NSS Kagoshima NSS Okinawa

Safety Notice

### ALTIA Co,. Ltd.

1-8-12 Harumi, Harumi Triton Square Z-6F, Chuo-ku, Tokyo 104-6206 Tel: 03 (6777) 0065

- Please note that specifications are subject to change without notice. Please contact your local sales company or Altia branch for ordering and consultation.

Sales outlet







